



PARKING LANE LINE
150mm WIDE

KERB AND CHANNEL

PROPERTY BOUNDARY

600mm WIDE DIAGONALS

ONE WAY RED RAISED REFLECTORIZED PAVEMENT MARKERS @ 24m SPACING ON NON TRAFFICABLE SIDE OF LANE LINE

10.00
10.00

12.00
6.00

3.0-4.0

PROPERTY BOUNDARY

KERB AND CHANNEL

LANE DIMENSIONS

- A = THROUGH LANES - 3m (DESIRABLE MIN.)
- B = PARKING LANES - BALANCE (DESIRABLE MIN. 2.1m TO FACE)
- C = 3m MIN.

ALL TRANSVERSE LINE AND PAVEMENT MARKINGS COLD APPLIED TROWELLED MATERIAL AND THERMOPLASTIC MATERIAL FOR ALL LONGITUDINAL LINEMARKING. (AS PER VICROADS STANDARDS)

NOTE: LINE MARKING TO BE IN ACCORDANCE WITH VICROADS TRAFFIC ENGINEERING MANUAL VOL.2 (SIGNS & LINE MARKING)



GREATER DANDENONG

STANDARD PARKING LANE AND CENTRELINE TREATMENT AT ROUNDABOUTS AND SCHOOL CROSSINGS

LAST UPDATED - SEPTEMBER 2014

INFRASTRUCTURE PLANNING

SD 710-A