



PARKING LANE LINE  
150mm WIDE

STANDARD SEPARATION LINE - 3m STRIP 9m GAP  
100mm WIDE WITH WHITE TWO WAY RAISED  
REFLECTORIZED PAVEMENT MARKERS @ 24m SPACING

ONE WAY RED RAISED REFLECTORIZED PAVEMENT  
MARKERS @ 24m SPACING ON NON TRAFFICABLE  
SIDE OF LANE LINE

ALL TRANSVERSE LINE AND PAVEMENT MARKINGS COLD  
APPLIED TROWELLED MATERIAL AND THERMOPLASTIC  
MATERIAL FOR ALL LONGITUDINAL LINEMARKING. (AS  
PER VICROADS STANDARDS)

NOTE: LINE MARKING TO BE IN ACCORDANCE WITH  
VICROADS TRAFFIC ENGINEERING MANUAL VOL.2  
(SIGNS & LINE MARKING)

LANE DIMENSIONS  
A = THROUGH LANES - 3m (DESIRABLE MIN.)  
B = PARKING LANES - BALANCE (DESIRABLE MIN. 2.1m TO FACE)



# GREATER DANDENONG

## STANDARD PARKING LANE AND CENTRELINE TREATMENT

LAST UPDATED - SEPTEMBER 2014

---

INFRASTRUCTURE PLANNING

---

SD 709-A