


ATTACH WITH 10mm DIA x 100mm CONTINUOUS THREAD LUG, DYNABOLT OR LIGATURES TO MANUF. RECOMMENDATIONS.

FIXING DETAIL

NOTES:

1. DIMENSIONS GIVEN ARE FOR STANDARD TYPE 1 AND TYPE 2 SIDE ENTRY PITS. FOR FITTING TO NON STANDARD PITS WITH DIFFERENT DIMENSIONS OR WITH DIFFERENT SETBACKS FROM BACK OF KERB, STEEL FRAME DETAILS WILL NEED TO BE MODIFIED TO ENSURE THAT FIXING BOLTS ARE LOCATED A MINIMUM OF 50mm FROM THE FACE (INTERIOR OR EXTERIOR) OF THE PIT WALL.
2. COMPOSITE PIT LID AND STEEL FRAME ARE TO BE AS SHOWN OR COUNCIL APPROVED EQUIVALENT, COMPLIANT WITH AS3996-2006 AND AS 4586-2004.
3. IN NATURE STRIPS PIT LIDS ARE TO COLOURED KHAKI GREEN. IN PLAIN COLOURED CONCRETE PAVING PIT LIDS ARE TO BE STORM GREY. MANUFACTURER CAN ARRANGE SUITABLE CUSTOM COLOUR TO MATCH OTHER PAVING SURFACE TYPES.



GREATER DANDENONG

**STANDARD PIT LID AND FRAME
FOR SIDE ENTRY PITS TYPE 1 AND 2**

LAST UPDATED - SEPTEMBER 2014

INFRASTRUCTURE PLANNING

SD 205-A